

Original post set 1820 by Hendricks with witnesses: 48" white oak N 12 W 21 links, 20" beech S 47 E 24 links per Marion County Atlas pg. 9. Hosbrook 2-19-1852 made no reference to any monument nor plats any stone at this location per Franklin Township Legal Survey Book pg. 24. Hosbrook 10-11-1886 called stone in description of a road he surveyed per Franklin Township Legal Survey Book pg. 56. 9-26-61 called stone beneath pavement. 8-25-68 called PK nail over stone. 12-7-71 gave new ties. 4-25-73 called stone beneath pavement. 4-18-75 called PK nail in can top over stone. 7-23-79 called PK nail. 4-6-80 called stone. 6-25-85 excavated and set Harrison. Re-tied 9-26-94 per Wilcoxen. Re-tied 7-29-99.

HC441402

| REF. | DISTANCE | DESCRIPTION  |
|------|----------|--|
| 1.   | 54.30′   | Top nut fire hydrant   |
| 2.   | 58.32'   | Face 2' steel post "flag pole"                                     |
| 3,   | 37,51′   | PK E PwP#91-766 48'up  |
| 4.   | 54.66′   | Southerly corner of most westerly conc. base "Piner Cemetery" sign |
| 5,   | 28.35′   | PK E PwP#16-766 12"up  |
|      |          |  |
|      |          |  |
|      |          |  |
|      |          |  |
|      |          |  |